

flow~mon

...simple flow solutions in a complicated world

Flapper & Spout Visual Sight Indicator

Where Visual Inspection is necessary our dual window sight indicator with flap and easy to read scale is an ideal plant safety device, with the sizeable viewing area allowing for good clear observation to check product quality, consistency, leak detection and general flow conditions.

The Flapper or Spout can be used in transparent or slightly opaque solutions and gas services. These units offer an inexpensive means of viewing the process to ensure that the stream is flowing or to note poor characteristics such as colour, turbulence and other properties that might indicate process deterioration or equipment malfunction. These Site Indicators can be mounted horizontally or vertically (up only for Flapper style).

Materials of Construction;



- Body & Covers** - Stainless Steel 316, Mild Steel or Bronze
- Glass** - Toughened Borosilicate or Sodalime
- Gaskets** - PTFE
- Flap** - Stainless
- Scale** - Polycarbonate (for Spout type Klingsill Gasket C4400)
- Fasteners** - Stainless A2

(Every effort will be made to meet any special connections and material requirements)

Pressure Rating >60Bar;

Sizes BSP, NPT, Socket Weld and Flanged connection

Small	1/4"(8)	3/8"(10)	1/2"(15)	3/4"(20)	1"(25)
Medium	1 1/4"(32)	1 1/2"(40)			
Large	2"(50)				




large

Materials of Construction;

- Body & Covers** - Stainless Steel 316, Mild Steel or Bronze
- Glass** - Toughened Borosilicate or Sodalime
- Gaskets** - PTFE
- Flap** - Stainless
- Scale** - Polycarbonate (for Spout type Klingersill Gasket C4400)
- Fasteners** - Stainless A2

(Every effort will be made to meet any special connections and material requirements)





Technical Information

Pressure Rating >60Bar;

Size	Min Flow	Max Flow	Dimensions (mm)						Scale (lpm)								
			Weight (kg)		Length		Width	Height	1	2	3	4	5	6	7	8	9
			T	F	T	F											
50	4	1000	9	15	150	220	170	110	6	9	12	15	23	28	33	50	75

T= Threaded F= Flanged



For further information contact:
 Tel: 01423 561972 Fax: 01423 502063
 Email: sales@flow-mon.com www.flow-mon.com
 Flow-Mon Limited, Chatworth House, Chatsworth Terrace,
 Harrogate, North Yorkshire HG1 5HT, UK