

9000 Mk2 Transmitter

Pressure & Hydrostatic Level Transmitter

Data sheet
0077

9000 transmitter

- Absolute and gauge pressure transmitters
- Good long-term stability
- Hygienic approval

Features

- 2 wire 24V dc loop powered
- 4 to 20mA output
- Accuracy +/- 0.1% of calibrated span
- Spans from 0.02 to 300 Bar
- 10:1 rangeability
- Ceramic capacitive sensor
- High overrange capability
- Temperature compensated
- Reverse polarity protection
- Wide range of process connections
- Intrinsically safe option

Description

The 9000 pressure transmitter is designed to perform in the arduous conditions of today's industrial measurement applications.

Using temperature compensated, surface mount electronics and a ceramic capacitive sensor, the 9000 provides an accuracy of better than +/-0.1% of calibrated span and excellent long term stability. One field replaceable PCB covers the entire product range and provides simple calibration over the 10:1 rangeability limits.

Available with a wide variety of process connection materials and configurations, the series 9000 offers wider application versatility than many of its higher priced rivals. All hygienic models carry the 3A hygienic approval.

Operation

At the heart of the 9000 is the Ceramic Capacitive Sensor (CCS). This ensures extremely low hysteresis, high repeatability and high overrange capabilities.

The CCS replaces the traditional metallic diaphragm and sensor assembly and provides outstanding resistance to chemical attack.

The CCS eliminates the need for oil filled isolation, ensuring better temperature stability and allowing process temperatures between -30°C to +125°C.

Advantages of ceramic capacitive sensor technology

- High overrange capability
- Better long term stability and overall performance.
- Low hysteresis and high repeatability.
- Highly corrosion resistant and no oil filling giving better temperature stability and eliminating process contamination.
- The CCS used in the 9000 series can directly withstand most process media with temperatures between -30°C and 125°C.



PRODUCT OVERVIEW

Threaded



Flanged



Hygienic



The 9000 transmitter gives high performance with accuracy better than 0.1%, temperature compensation and excellent long term stability, the 9000 ensures precise and reliable measurement and is virtually maintenance free.

Compact, low mass

Weighing less than one kilogram, the 9000 is designed for "direct to process" mounting hence reducing installation costs. The sensor housing contains the ceramic capacitance sensor and the electronics circuit board, all the components needed to produce an accurate and reliable measurement of the process.

Protected from aggressive environments and processes

The transmitter is designed to withstand the harshest of environments. The housing is environmentally protected to the requirements of IEC IP67. Its rugged ceramic sensor is inherently capable of withstanding attack from most chemicals. Normal process temperature limits are -30 and +125°C, ambient temperature limits are -20 to +90°C (80°C EEx ia) Overrange limit is up to 5 times upper range limit, depending upon the sensor selected.

Optional process connections

Where necessary, flanged or sanitary process connections of various materials are available suitable for use in food and beverage applications. Alternative process connections are available on request.

The Sensor

All members of the 9000 family use a Capacitive Ceramic Sensor (CCS), manufactured using an aluminium oxide ceramic. The sensor measuring range is determined by the thickness of the ceramic, this is precisely controlled during the manufacturing process. The CCS works like a capacitor with electrode surfaces on the inside comprising one measuring and one reference capacitor. The surfaces of the capacitor are gold plated and linked to ASIC electronics. These electronics generate a signal proportional to the applied pressure, which is sent to the 4-20mA signal conditioner.

The ceramic sensor is a "dry cell" meaning no isolating diaphragm and fill fluid is needed. The process fluid acts directly onto the rugged, corrosion resistant sensor.

Other members of the 9000 family

- 9710** - Cable suspended, submersible level.
- 9720** - Clamped, submersible level.
- 9780** - Pole mounted, submersible level.
- 9790** - Flange mounted submersible level
- 9795** - "Thames" style ¾" BSPP running nut
- 9797** - 1½" BSPP male, submersible

For further information, ask for data sheet number 0078

ORDERING INFORMATION : INDUSTRIAL VERSION

9000		Gauge & absolute pressure transmitters - Industrial versions								
		Code		Enclosure						
		S		Stainless steel (316)						
		A		Aluminium bronze						
		Code		O ring	Process temperature limits (Note 3)					
		1		Viton	-20 to + 125°C					
		2		Buna N	-30 to + 110°C					
		3		Chemraz	-30 to + 110°C (non-wetted 'O' rings in Viton) (Note 5)					
		4		EPDM	-30 to + 125°C					
		Code		Nominal range			Overrange limit (Note 1)			
		GB		0 to 0.1 Bar g (0 to 1m H ₂ O)			0.5 Bar g			
		GC		0 to 0.2 Bar g (0 to 2m H ₂ O)			1 Bar g			
		GD		0 to 0.5 Bar g (0 to 5m H ₂ O)			2.5 Bar g			
		GE		0 to 1.0 Bar g (0 to 10m H ₂ O)			5 Bar g			
		GF		0 to 2.0 Bar g (0 to 20m H ₂ O)			10 Bar g			
		GG		0 to 5.0 Bar g (0 to 50m H ₂ O)			25 Bar g			
		GH		0 to 10 Bar g (0 to 100m H ₂ O)			30 Bar g			
		GJ		0 to 20 Bar g (0 to 200m H ₂ O)			60 Bar g			
		GK		0 to 70 Bar g			105 Bar g			
		GL		0 to 300 Bar g			400 Bar g			
		AA		0 to 0.1 Bar a			1 Bar a			
		AB		0 to 0.2 Bar a			1 Bar a			
		AC		0 to 0.5 Bar a			2.5 Bar a			
		AD		0 to 1.0 Bar a			5 Bar a			
		AE		0 to 2.0 Bar a			10 Bar a			
		AF		0 to 5.0 Bar a			25 Bar a			
		AG		0 to 10 Bar a			30 Bar a			
		AH		0 to 20 Bar a			60 Bar a			
		AJ		0 to 70 Bar a			105 Bar a			
		AK		0 to 300 Bar a			400 Bar a			
		Code		Approval						
		0		Non certified - Safe area use only						
		1		ATEX II 1 G and ATEX II 1 D EEx ia IIB T4						
		Code		Process connection (Note 2)			Max. pressure			
		AB		1/2" NPT male & 1/4 NPT female			400 bar			
		BC		1/2" BSPT male & 1/4" BSPT female			400 bar			
		AC		1/4" NPT male			400 bar			
		AD		G 1/2"- A (1/2" BSPP male)			400 bar			
		AE		G 1 1/2" A (1 1/2" BSPP male)			400 bar			
		AF		Hygienic 1 1/2" Tri-Clamp			40 bar			
		AG		Hygienic 2" Tri-Clamp			40 bar			
		AH		Hygienic 1 1/2" IDF			16 bar			
		AJ		Hygienic 2" IDF			16 bar			
		AK		Hygienic 1 1/2" RTJ			10 bar			
		AL		Hygienic 2" RTJ			10 bar			
		BD		Hygienic 1 1/2"(38mm) SMS			16 bar			
		BE		Hygienic 2"(51mm) SMS			16 bar			
		BM		Hygienic 2"(51mm) SMS			16 bar			
		AM		Slip on flange DN25 PN40 (DIN2635)			40 bar			
		AN		Fixed flange DN50 PN40 (DIN2635)			40 bar			
		AP		Fixed flange DN80 PN40 (DIN2635)			40 bar			
		AQ		Slip on flange 1" #150 (ANSI B16.5 RF)			18.4 bar			
		AR		Fixed flange 2" #150 (ANSI B16.5 RF)			18.4 bar			
		AS		Fixed flange 3" #150 (ANSI B16.5 RF)			18.4 bar			
		Code		Process connection material						
		1		Stainless Steel 316 S31						
		3		Aluminium bronze						
		4		Titanium (fittings in 316SS)(Codes AB to BE - Note 6)						
		5		Titanium (flanges in 316SS)(Codes AM to AS - Note 6)						
		Code		Temp barrier (note 3)						
		X		No						
		A		Yes						
9000	S	2	GB	1	AB	1	X	Typical ordering code		

- Notes:
1. Overrange limit of sensor shown. Process connection may reduce permitted overrange.
 2. Temperature barrier recommended for hygienic application. Max. pressure stated is for connection, not sensor.
 3. Used to reduce risk of condensation forming in electronics housing when combination of low process and high ambient temperature is possible. Also required when process temperature may exceed 90°C
 4. Check relevant flange tables if temperature is greater than 50°C.
 5. Not available on fixed flange versions
 6. Fixed flange on Aluminium Bronze option

ORDERING INFORMATION : MARINE VERSION

9000M		Gauge pressure transmitters - Marine versions					
	Code	Enclosure					
	S	Stainless steel (316)					
	A	Aluminium bronze					
	Code	O ring					
	1	Viton					
	2	Buna N					
	Code	Nominal Range			Overrange limit		(Note 1)
	GC	0 to 0.2 Bar g (0 to 2m H ₂ O)			1 Bar g		
	GD	0 to 0.5 Bar g (0 to 5m H ₂ O)			2.5 Bar g		
	GE	0 to 1.0 Bar g (0 to 10m H ₂ O)			5 Bar g		
	GF	0 to 2.0 Bar g (0 to 20m H ₂ O)			10 Bar g		
	GG	0 to 5.0 Bar g (0 to 50m H ₂ O)			25 Bar g		
	GH	0 to 10 Bar g (0 to 100m H ₂ O)			30 Bar g		
	GJ	0 to 20 Bar g (0 to 200m H ₂ O)			60 Bar g		
	Code	Electrical Approval					
	0	Non certified - Safe area use only					
	1	ATEX II 1 G EEx ia IIB T4					
	Code	Process connection			Max. pressure		
	AB	1/2" NPT male & 1/4" NPT female			400 bar		
	AC	1/4" NPT male			400 bar		
	AD	G 1/2"- A (1/2" BSPP male)			400 bar		
	AE	G 1 1/2" A (1 1/2" BSPP male)			400 bar		
	AM	Slip on flange DN25 PN40 (DIN2635)*			40 bar		
	AN	Fixed flange DN50 PN40 (DIN2635)			40 bar		
	AP	Fixed flange DN80 PN40 (DIN2635)			40 bar		
	AQ	Slip on flange ANSI B16.5 1" # 150			18.4 bar		
	AR	Fixed flange ANSI B16.5 2" # 150			18.4 bar		
	AS	Fixed flange ANSI B16.5 3" # 150			18.4 bar		
	Code	Process connection material					
	1	Stainless Steel 316 S31					
	3	Aluminium bronze					
	4	Titanium					
	Code	Temp barrier					
	X	No					
9000M							Typical ordering code

Notes:

1. Overrange limit of sensor shown. Process connection may reduce permitted overrange.

* Fixed flange on Aluminium Bronze option

Marine Approvals :-

Lloyds Register

Germanischer Lloyd

Det Norske Veritas

Bureau veritas

American Bureau of Shipping

Registrano Italiano

Korean Register

SPECIFICATION

Functional

Process fluid: Liquid, gas & vapour	Zero adjustment:	-20% to +40% of span
Output signal: Two-wire, 4-20mA	Span adjustment:	10% to 100% of URL*
Power supply: 10-30 Vdc	Process temp. limits:	See ordering information
Load resistance: $R = 50 \times (\text{supply voltage} - 10\text{v})\Omega$	Ambient temp. limits:	-20°C to +90°C
Measuring range: 0.01 to +300 bar	Humidity limits:	(+80°C EEx ia)
OVERRANGE limit: See ordering information	Hazardous area certification:	0 to 100% RH
		ATEX II 1 G and ATEX II 1 D
		EEx ia IIB T4
		(Ta = -30°C to +80°C)

* 20% to 100% on 0.1 bar and 0.2 bar ranges

Performance

Accuracy: +/- 0.1%• of calibrated span including linearity, hysteresis and repeatability
Stability: +/- 0.1% URL* per 6 months
Temperature effect: +/- 0.015% URL* per °C (over ambient temperature range)

•All nominal ranges except 300 bar, which is +/- 0.5%

* URL = Upper Range Limit (Maximum span)

Physical

Electrical connection: M20 cable gland for cable O.D. 5 to 9mm	Non-wetted parts: Housing:	316 St Steel or Aluminium Bronze
Process connection: See ordering information	Body 'O' rings:	Viton or Buna
Wetted Parts: Sensor Ceramic	Humidity limits: 0 to 100%	0 to 100%
Process conn: 316 St Steel, aluminium Bronze or Titanium	Ingress protection: IP67	IP67
Face seal ring: Viton, Buna N, EPDM or Chemraz #	Approximate weight: 1 Kg (threaded version)	1 Kg (threaded version)

EPDM and Chemraz only available on industrial versions

APPROVALS

Hazardous Area Certification :-

ATEX II 1 G
ATEX II 1 D (90°C)
EExia IIB T4 Intrinsically Safe
(Ta = -30°C to + 80°C)

Hygienic:-

3A's Hygienic Approval

Marine Approvals :-

Lloyds Register
Germanischer Lloyd
Det Norske Veritas
Bureau veritas
American Bureau of Shipping
Registrano Italiano
Korean Register

KDG Instruments

Crompton Way Crawley West Sussex UK RH10 9QR
Tel: 01293 866000 Fax: 01293 530849
e-mail: sales@solartron.com www.solartronmobrey.com

Head Office

Solartron Mobrey Limited

158 Edinburgh Avenue Slough Berks UK SL1 4UE
Tel: 01753 756600 Fax: 01753 823589

Solartron Mobrey GmbH	Deutschland	tel: 0211/99 808-0
Solartron Mobrey sp z o o	Polska	tel: 022 871 7865
Solartron Mobrey AB	Sverige	tel: 08-725 01 00
Solartron Mobrey SA	France	tel: 01.30.17.40.80
Solartron Mobrey SA-NV	Belgium	tel: 02/465 3879
Solartron Mobrey Ltd	China	tel: 021 6353 5652
Solartron Mobrey	USA	tel: (281) 398 7890



The right is reserved to
amend details given in this
publication without notice



a Roxboro Group Company

0077
June 04